## Type 251D MiniKlassik stainless steel perforated grate (ADA)





#### **Product Features**

- Certified to EN 1433 Load Class A 3,500 lbs 70 psi
- Uses 'DrainLok' boltless locking system
- Suitable for use with K50/KS50
- Manufactured from 16 gauge, grade 304 stainless steel
- Complies with ADA American Disabilities Act of 1990 Section 4.5.4
- Complies with ASME: A112.6.3 2001: Section 7.12 Heel Resistant Strainers and Grates
- Bicycle Tire Penetration Resistant to AS3996-2006



### **Specifications**

#### General

The surface drainage system shall be ACO Drain MiniKlassik K50/KS50 channels complete with ACO MiniKlassik stainless steel perforated grate as manufactured by ACO, Inc. or similar approved.

#### Materials

The covers shall be manufactured from stainless steel and have **minimum** properties as follows:

- Independently certified to meet Load Class A to EN 1433 - 3,500 lbs - 70 psi
- 16 gauge, grade 304 stainless steel
- Intake area of 14.5 sq. in. (93.5 cm²) per meter grate

The overall width of 2.89" and overall length of 39.37". Perforations measure 0.23" (5.84mm) in diameter.

#### Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.







## Type 251D MiniKlassik stainless steel perforated grate (ADA)

# 

#### Plan view




# **Side elevation**



Description	Part No.	Length inches <i>(mm)</i>	Width inches (mm)	Weight lbs.
Type 251D MiniKlassik Stainless steel perforated grate	138101	39.37 (1000)	2.89 (73.4)	4.0

#### 'DrainLok' locking mechanism



ACO DrainLok™ is a patented, boltless locking system that removes the need for bolts and bars and improves the hydraulic capacity of the channel. The  $\mathsf{DrainLok^{\mathsf{TM}}}\ \mathsf{mechanism}\ \mathsf{simply}$ clips into the channel edge rail for rapid installation. ACO DrainLok™ grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.

#### ACO, Inc. **Northeast Sales Office** 9470 Pinecone Drive

Mentor, OH 44060 Tel: (440) 639-7230 Toll free: (800) 543-4764 Fax: (440) 639-7235

#### **West Sales Office**

825 W. Beechcraft St. Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899

#### **Southeast Sales Office**

4211 Pleasant Road Fort Mill, SC 29708 Toll free: (800) 543-4764 Fax: (803) 802-1063

#### Follow us on f B Time



www.ACODrain.us



© April 2018, ACO, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO, Inc. Reorder# DL163 reserves the right to change the product and specifications without notice.