


Product Features

- Certified to EN 1433 Load Class B - 28,000 lbs - 581 psi
- Uses 'DrainLok' boltless locking system
- Suitable for use with K100, KS100, H100-8, H100-10, H100K-8 and H100KS-8 channels
- Manufactured from 16 gauge, galvanized steel
- Complies with ADA - American Disabilities Act of 1990 Section 4.5.4
- Bicycle Tire Penetration Resistant to AS 3996 - 2006



ACO Specification Information

Specifications

General

The surface drainage system shall be ACO Drain K100, KS100, H100-8, H100-10, H100K-8 or H100KS-8 channels complete with ACO Type 438D/437D longitudinal galvanized steel grate with 'DrainLok' locking as manufactured by ACO Polymer Products, Inc. or similar approved.

Materials

The covers shall be manufactured from galvanized steel and have **minimum** properties as follows:

- **Independently certified to meet Load Class B to EN 1433 - 28,000 lbs - 581 psi**
- **16 gauge galvanized steel**
- **Intake area of 33.0 sq. in. (212.90 cm²) per half meter of grate**

The overall width of 4.84" (123 mm) and overall length of 39.37" (1000 mm) (Type 438D) and 19.69" (500 mm) (Type 437D). Slots measure 1.15" x 0.3" (29.21 mm x 7.62 mm).

Installation


The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

ACO DRAIN


Type 438D/437D Galvanized steel longitudinal grate (ADA)



Plan view




Side elevation



Description	Part No.	Length inches (mm)	Width inches (mm)	Weight lbs.
PowerLok grate				
Type 438D Galvanized steel longitudinal grate	132555	39.37" (1000)	4.84 (123)	10.0
Type 437D Galvanized steel longitudinal grate	132550	19.69" (500)	4.84 (123)	4.2

'DrainLok' locking mechanism



ACO DrainLok™ is a patented, boltless locking system that removes the need for bolts and bars and improves the hydraulic capacity of the channel. The DrainLok™ mechanism simply clips into the channel edge rail for rapid installation. ACO DrainLok™ grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.

ACO Polymer Products, Inc.

Northeast Sales Office

9470 Pinecone Drive
Mentor, OH 44060
Tel: (440) 639-7230
Toll free: (800) 543-4764
Fax: (440) 639-7235

West Sales Office

825 W. Beechcraft St.
Casa Grande, AZ 85122
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-9899

Southeast Sales Office

4211 Pleasant Road
Fort Mill, SC 29708
Toll free: (800) 543-4764
Fax: (803) 802-1063

Follow us on



Electronic Contact:

info@ACODrain.us
www.ACODrain.us



© August 15, 2016 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products Inc. reserves the right to change the product and specifications without notice.